


# uniflex Party and Exhibition Hall

## Type: 30,4/340 · Model: 342



### Measures/Weights

Width	(A)	30,13	m
Eave height	(C)	3,25	m
Ridge height	(D)	8,14	m
Gable truss	(B1)	5,06	m
Gable truss	(B2)	5,00	m
Distance between trusses	(B3)	5,00	m
Membrane peak			m
Roof slope		18,00	degrees
Longest frame component		10,60	m
Truss profile		250 x 120	mm
Ridge and eave purlin		100 x 80	mm
Intermediate purlin		80 x 80	mm
Frame and PVC-fabrics		7,00	sqm

### Technical description

#### Aluminium Profiles

out of solid, hard pressed  
4-groove aluminium hollow profile

#### Steel parts

hot-dip galvanized according to  
DIN 50976,  
extremely corrosion-resistant


#### Ground anchoring

Ground stakes

### Load requirements/Technical data

Wind load	0,50	kN/sqm
Wind speed	100,00	m/h
Minimum assembly length	10,00	m
Maximum assembly length	unlimited	
	in 5 m	increments

Losberger Intertent GmbH  
Gottlieb-Daimler-Ring 14  
D-74906 Bad Rappenau  
Tel.: +49(0)7066/980-0 · Fax: 980232  
eMail: Losberger@Losberger.com  
www.Losberger.com



**LOSBERGER**